

SteryIPlus

ADDITIVE FOR PAINTING AND PANELING, PREVENTS THE GROWTH OF MOLD AND MILDEW

TECHNICAL DATA SHEET n. INT/su/05

www.oikos-group.it/sterylplus

Technical Qualities

STERYLPLUS by OIKOS is a special concentrated, additive that comes in the form of a dense liquid containing active principles that are extremely effective at blocking the growth of a very wide range of mould, algae, mildew and lichen on painted surfaces, making it highly efficient as a preventive measure. STERYLPLUS, added to either interior or exterior paints, increases the products resistance to the growth of micro organisms on the wall.

Ideal Use

As an anti mould additive in all types of interior and exterior paint.

Application Method

Pour STERYLPLUS directly into the interior or exterior, water based paint that is to be used in the following ratio: 0,25lt of STERYLPLUS in 4÷5lt of product. or the container of 0.750 l into 14÷15 l of the paint to be treated. Mix evenly and proceed to apply the treated paint as normal.

The product

Composition	Mixture of active principles in water
Specific weight	1 Kg/l ±3%
pH	7 ÷ 11
Viscosity	5,000 ÷ 11.000 CPS Brookfield (RVT 20 revs/min. a 25°C)
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Reaction to fire	Negative when the product is applied onto a non inflammable surface: water based material with dry thickness of less than 0,600mm
Packaging	0,25 -0,75 l

The application

Dilution	Add 0,25lt of STERYLPLUS every 4 – 5 lt of paint. 0,75lt in 14 – 15 lt of paint
Tools cleaning	Water

Safety information

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is classified as hazardous pursuant to the provisions set forth in the Regulations (CE) 1272/2008 (CLP) and subsequent amendments and supplements. For further information see the product Safety Data Sheet. No special arrangements are required for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements

Specifications

Pour the content of the container of a concentrated additive of the kind of STERYLPLUS by OIKOS of a capacity of into a bucket of paint of a capacity of..... Mix the paint with the additive and proceed with painting. All must be carried out in accordance with the norms of application, at a cost of mq inclusive of materials and labour.