

TECHNICAL DATA SHEET

----- PAINT DIVISION -----

Novalis Paint Stripper

sez. 1.0 Technical characteristic

NOVALIS PAINT REMOVER by OIKOS is a special product able to remove every type of synthetic paint from every type of surface. It can remove several coats of paint at a time with an action time of between 1 and 24 hours. The fact that there are no odours or emissions from the product, make its use extremely easy also in aerated interiors, without the need for special precautions. It has a low odour level, is non inflammable and friendly to both humans and the environment.

sez. 2.0 Ideal Use

Stripping of paints and enamels.

sez. 4.0 Application method

Apply, by brush or trowel, NOVALIS PAINT REMOVER onto the surface to be treated. Leave to act for 1 ÷ 24 hours depending on the material to be removed. Following this proceed to scrape the surface using either a scraper or a trowel. Wash the treated surface with water.

sez. 6.0 Technical Characteristic: application

Dilution	Ready to use
Yield	2 ÷ 3 m ² /l on enamels and smooth paints; 1 ÷ 2 m ² /l on textured coatings and thick paints
Application tools	brush, trowel for application; trowel or scraper for removal
Application temperature	+5°C ÷ +36°C (relative humidity not higher than 80%)
Drying time: tack free	2 ÷ 4 h (temperature= 20°C humidity not higher than 75%)
Tools cleaning	Water

sez. 7.0 Technical Characteristic: the product

Composition	mix of water and high boiling point ecological substances.
Specific weight	1kg/l +/-3%
pH	7÷8
Viscosity	10.000 ÷ 20.000 +/-5% CPS Brookfield (RVT 20 revs/min at 25°C)
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Packaging	0,75 – 2.25 – 3.75l

sez 8.0 Toxicological data

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is considered to be a non dangerous substance if used in the technically correct manner. Normal cautionary measures for the handling of water based paints are advised. No special arrangements are required for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements.

sez. 9.0 Specifications

Apply a water based paint stripper such as NOVALIS PAINT STRIPPER by OIKOS in accordance with the norms of application, at a cost ofmq. inclusive of materials and labour. Scaffolding not included.

Note

The company Oikos S.r.l guarantees, to the best of its own technical and scientific knowledge, that the information contained in this technical data sheet is correct.

Notwithstanding that indicated above, Oikos takes no responsibility for the results obtained through the use of this product in as much as it is not possible for Oikos to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.