

TECHNICAL DATA SHEET

----- PAINT DIVISION -----

SterylSan

sez. 1.0 Technical characteristic

STERYLSAN by OIKOS is a revitalising and sanitising product for interior and exterior walls suffering with mould and algae contamination. It is a product prepared using a range of active ingredients that work against all kinds of micro organisms in the surface, thanks to its ability to penetrate deep inside the support. It does not wash away with water and maintains its anti mould action over time.

sez. 2.0 Ideal Use

Interior and exterior surfaces with problems of mould and algae.

sez. 3.0 Surface preparation

On substrates that are already affected by mould and algae, remove and neutralise any micro organisms by applying a coat of STERYLFIX by OIKOS.

sez. 4.0 Application method

Apply a coat of STERYLSAN by OIKOS undiluted, using a brush or roller to perfectly revitalize the wall. Leave the product on the wall for at least 6-8 hours before proceeding to paint. This allows the full sanitizing of the wall even deep in the surface.

sez. 6.0 Technical Characteristic: application

Dilution	Ready to use, 10-15% with water in case of poorly absorbent walls.
Yield	8-10 m ² /l
Application Tools	Brush or roller
Application temperature	+5°C ÷ +36°C (with relative humidity not exceeding 80%)
Drying time: painting over	6-8 hours (temperature =20°C with relative humidity less than 75%)
Tools cleaning	Water

sez. 7.0 Technical Characteristic: the product

Composition	Water and ecological active ingredients
Specific weight	1 Kg/l ±3%
Ph	4.5-5.5
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Fire reaction	Negative when the product is applied onto a non flammable surface: water based material with dry thickness of less than 0,600 mm
Packaging	1 - 4 lt

sez 8.0 Toxicological data

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. Read carefully the safety data sheet: the product is labelled : Xi R43, R51/53. the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements

sez. 9.0 Specifications

On surfaces already contaminated my mould and algae, neutralize and remove any micro organisms using a detergent such as STERYLFIX by OIKOS. Following this apply, by brush or roller, a coat of a revitalizing product such as STERYLSAN by OIKOS. All must be carried out in accordance with the norms of application, at a cost of m² inclusive of materials and labour.

Note

The company Oikos S.r.l guarantees, to the best of its own technical and scientific knowledge, that the information contained in this technical data sheet is correct. Notwithstanding that indicated above, Oikos takes no responsibility for the results obtained through the use of this product in as much as it is not possible for Oikos to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.