

TECHNICAL DATA SHEET

----- Paint Division -----

SteryPlus

Product characteristicssez. 1

STERYLPLUS by OIKOS is a special concentrated, additive that comes in the form of a dense liquid containing active principles that are extremely effective at blocking the growth of a very wide range of mould, algae, mildew and lichen on painted surfaces, making it highly efficient as a preventive measure. STERYLPLUS, added to either interior or exterior paints, increases the products resistance to the growth of micro organisms on the wall.

Ideal usesez. 2

As an anti mould additive in all types of interior and exterior paint.

Application method sez. 4

Pour STERYLPLUS directly into the interior or exterior, water based paint that is to be used in the following ratio: 0,25lt of STERYLPLUS in 4÷5lt of product. or the container of 0.750 l into 14÷15 l of the paint to be treated. Mix evenly and proceed to apply the treated paint as normal.

Technical characteristics: the applicationsez. 6

Dilution	Add 0,25lt of STERYLPLUS every 4 – 5 lt of paint. 0,75lt in 14 – 15 lt of paint
Tools cleaning	Water

Technical characteristics: the productsez. 7

Composition	Mixture of active principles in water
Specific weight	1 Kg/l ±3%
Ph	7-11
Viscosity	5,000 ÷ 11.000 CPS Brookfield (RVT 20 revs/min. a 25°C)
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Fire reaction	Negative when the product is applied onto a non inflammable surface: water based material with dry thickness of less than 0,600 mm
Packaging	0.25 - 0.75 l

Toxicological data.....sec. 8

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. Read carefully the safety data sheet: the product is labelled : Xi R43, N R50/53. the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements

Specificationssec. 9

Pour the content of the container of a concentrated additive of the kind of STERYLPLUS by OIKOS of a capacity of into a bucket of paint of a capacity of..... Mix the paint with the additive and proceed with painting. All must be carried out in accordance with the norms of application, at a cost of mq inclusive of materials and labour

Note

The company Oikos S.r.l guarantees, to the best of its own technical and scientific knowledge, that the information contained in this technical data sheet is correct. Notwithstanding that indicated above, Oikos takes no responsibility for the results obtained through the use of this product in as much as it is not possible for Oikos to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.