

## TECHNICAL DATA SHEET

# STERYLFIX

### Technical Qualities

STERYLFIX by OIKOS is a special colourless cleansing solution that quickly eliminates mould, algae and mildew from affected walls, and at the same time exerts a neutralizing effect. The products formulation allows it to eliminate all traces of mould that appear in the more humid areas of the wall. STERYLFIX, apart from being used on walls, is also highly efficient when used on the joins between floor tiles, shower curtains and in general on areas which are particularly humid such as bathrooms, saunas, kitchens, cellars and laundries.

### Ideal Use

Interior and exterior surfaces with problems of mould and algae.

### Application Method

Using a brush or a spray pump, apply the product directly onto the surface to be treated. Following this, using a sponge or a scraper, remove the mould and algae from the surface. If necessary, it is possible to repeat the operation to ensure that the wall is thoroughly clean.

### Technical Characteristics: Application

Dilution	Ready to use
Yield	8-10 m <sup>2</sup> /l
Application Tools	Brush or spray pump
Application temperature	+5°C ÷ +36°C (with relative humidity not exceeding 80%)
Drying time: painting over	4-6 hours (temperature =20°C with relative humidity less than 75%)
Tools cleaning	Water

### Technical Characteristics: Product

Composition	Oxidizing chemical
Specific weight	1 Kg/l ±3%
Ph	11-12
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Fire reaction	Negative when the product is applied onto a non inflammable surface: water based material with dry thickness of less than 0,600 mm
Packaging	L 1

## **Safety information**

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is classified as hazardous pursuant to the provisions set forth in the Regulations (CE) 1272/2008 (CLP) and subsequent amendments and supplements. For further information see the product Safety Data Sheet. No special arrangements are required for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements

## **Specifications**

Apply on surfaces contaminated by moulds and algae a special cleansing solution such as STERYLFIX by OIKOS. Then remove the mould and algae from the surface using a sponge or brush. It is possible to apply the product a second time to complete the cleaning. All must be carried out in accordance with the norms of application, at a cost of ..... m2. inclusive of materials and labour.

*The company Oikos S.r.l guarantees, to the best of its own technical and scientific knowledge, that the information contained in this technical data sheet is correct.*

*Notwithstanding that indicated above, Oikos takes no responsibility for the results obtained through the use of this product in as much as it is not possible for Oikos to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.*